

# A STUDY ON “PLASTIC WASTE MANAGEMENT”

**Ms. Aarti Paunekar & Mr. Damini Patil**  
**Final Year BHMCT**  
**Tuli College of Hotel Management**

## INTRODUCTION

Waste is now a global problem, and one that must be addressed in order to solve the world's resource and energy challenges.

Plastic is a material in any of a wide range of synthetic or semi synthetic that are moldable. These are made from limited sources of petroleum. Huge advances are being made in the development of technologies to recycle plastic waste among other resources. Plastics have made significant contribution in almost every field of human activity today – agriculture, medical, transportation, piping, electrical and heat insulation, packaging, manufacturing of household and electronic goods, furniture and other items of daily or specific use. Plastics in medical products like disposable syringes, blister packing of tablets and capsules, joint replacement prostheses, inter venous (IV) fluid bottles, blood bags, catheters, heart valves, etc., have significantly helped supporting the human life. Medical devices made of plastics are implanted into the human body.

Contribution of plastics to human health is difficult to ignore. Plastic based packaging with the above-mentioned properties ensures reaching the best, hygienic and unadulterated product to the masses. The solution to waste management problem lies in segregation of dry and wet solid waste at the source for which an effective mass awareness campaign is very important. Creation of efficient solid waste management infrastructure coupled with encouraging establishment of recycling centres would help address the MSW problem. Plastics can be recycled to produce articles for mass use augmenting the concept of resource management. Many useful products have been developed with recycled plastics and large number of people is employed in these activities in small, micro and informal sectors. An informal industry estimate put the recycling figure of India at around 1.5 Million Tons – close to 50% of plastics used for packaging applications. This is a very high recycling ratio. Recycling ensures that the unwanted and discarded plastics waste does not remain in road side nor it is carried to the landfill.

### **Why recycle plastic?**

It gives to energy savings and the reduction of greenhouse gas emissions. It also saves non renewable sources like oil and gas. In addition to that, recycling provides livelihood for millions of people and families in developing countries, employment or informal economic activities

## **REVIEW OF LITERATURE**

### **Types of Plastics and their Major Applications**

The various types of plastics and their major applications are as follows:

Thermoplastics: These types of plastics become soft when heated, they can be moulded or shaped with pressure when in plastic state and, when cooled, they solidify and retain the shape or mould.

Some common thermoplastics with their uses and properties are as follows: -

Polyethylene terephthalate (PET): Some common properties are: **i.** Tough and clear, good strength and stiffness, chemical and heat resistant, good barrier properties for oxygen and carbon dioxide. **ii.** It is used in packaging, soft drink and mineral water bottles, fibers for clothing, films, food containers, transport, building and appliance industry (as it is fire resistant), etc.

High density polyethylene (HDPE): Some common properties: **i.** Good process ability, excellent balance of rigidity and impact strength, excellent chemical resistance, crystalline, melting point (130-135°C), and excellent water vapour barrier properties. **ii.** Used for making blow moulded products (various types of containers, water bottles), pipes, injection moulded products (storage bins, caps, buckets, mugs), films (carrier bags), etc.

Polyvinyl chloride (PVC): Its properties are: **i.** Versatility, energy saving, adaptability to changing time and environment, durability, fire resistance. **ii.** It is used in industries such as building and construction, packaging, medical, agriculture, transport. Also used for making wires and cables, furniture, footwear, domestic appliances, films and sheets, bottles, etc.

Low density polyethylene (LDPE): Characteristics of LDPE are: **i.** Easy process ability, low density, semi crystalline nature, low melting range, low softening point, good chemical resistance, excellent dielectric properties, low moisture barrier, poor abrasion and stretch resistance. **ii.** It is used for making carrier bags, heavy duty bags, nursery bags, small squeeze bottles. Also used in milk packaging, wire and cable insulation, etc.

Polypropylene (PP): Properties are: **i.** Low density, excellent chemical resistance, environmental stress resistance, high melting point, good process ability, dielectric properties, low cost, creep resistance. **ii.** Used for making bottles, medical containers, pipes, sheets, straws, films, furniture, house wares, luggage, toys, hair dryer, fan, etc.

Polystyrene (PS): Some of the properties of polystyrene are: **i.** Glassy surface, clear to opaque, rigid, hard, high clarity, affected by fats and solvents. **ii.** Used for making electrical and communication equipment's e.g. plugs, sockets, switch plates, coil forms, circuit boards, spacers and housings. Also used for making containers, toys, wall tiles, baskets, cutlery, dishes, cups, tumblers, dairy containers, etc.

Others plastics: There are many other types of plastics except these six types, often used in the engineering sector. Examples include polycarbonate (PC), nylon, and acrylonitrile butadiene styrene (ABS).

Thermosets: Thermosetting materials are those which once set cannot be remoulded/softened by applying heat. It includes phenol, melamine and urea formaldehyde, unsaturated polyester, epoxy and polyurethanes. These materials are not recyclable.

The management of plastic waste is to be planned in such a manner that the plastic waste generated from various sources is suitably taken care of.

### Conventional Technology for Plastic Waste Management

The conventional technology for plastic waste management involves recycling, landfilling and incineration.

Recycling of plastics through environmentally sound methods: Recycling of plastics must be carried out in such a manner that it minimizes the pollution level throughout the process and, as a result, increase the efficiency of the process and conserve the energy. Plastic recycling technologies have been divided into four general types-primary, secondary, tertiary and quaternary.

Primary recycling includes processing of scrap/waste into a product with features similar to the original product.

Secondary recycling involves processing of waste plastics into products that have characteristics dissimilar from those of original plastic products.

In Tertiary recycling, basic chemicals and fuels are produced from plastic scrap as part of the municipal waste stream or as a segregated waste.

Quaternary recycling reclaims the energy content of the scrap plastics by burning/incineration. This process is not in use in India.

Steps Involved in the Recycling Process are: Selection The recyclers need to select the wastes which are suitable for recycling.

Segregation : The plastic waste need to be segregated as per the codes stated in the BiS guidelines (IS:14534:1998).

Processing After selection and segregation, the pre-consumer waste shall be recycled directly. The post consumer waste (used plastic waste) shall be washed, shredded, agglomerated, extruded and granulated.

**Landfilling:** This is a traditional approach to waste management, but space for constructing landfills is becoming limited in some countries. A well-managed landfill site results in restricted instant environmental harm further than the impacts of collection and transportation, though there are long-term threats of contamination of groundwater and soil by few additives and breakdown by plastics products, which can turn out to be constant organic pollutants<sup>1</sup>. A main drawback of landfills from a sustainability feature is that no one of the material resources used for the production of plastic is recovered—the material flow is linear rather than cyclic. In U. K., a landfill tax is functional, which is currently set to rise every year so as to increase the incentive to turn away wastes from landfill to recovery actions<sup>2</sup>.

**Incineration:** This process lessens the need for landfilling of plastics wastes, but, there are worries that hazardous materials may be released into the atmosphere during this process. For example, halogenated additives and PVC are usually present in mixed plastic waste which leads to the threat of dioxins, furans and other polychlorinated biphenyls being released into the environment<sup>3</sup>. The choice of incinerators is very important. Though it is not likely to be done in a controlled manner so as to reduce the pollution due to off-gas i.e. dioxins and furans to wanted standards. So this method of plastic waste management is usually not preferred. The treatment cost of the gases is frequently more than the energy recovered.

Modern incineration technology has answers to tackle any incineration problem without polluting the environment and, in many cases, recovering the calorific value out of the waste being incinerated. Heavily contaminated plastic waste collected from different waste streams can be utilized for energy recovery by waste incineration plants. Cost of this system of recovery is considered highest among all the other alternatives. When considering incineration as an option, it is to be remembered that plastic waste incineration may lead to generation of harmful pollutants like dioxins and furans, which is highly undesirable.

## **Recent Technologies for Plastic Waste Management**

The recent technologies for plastic waste management are listed here.

**Polymer Blended Bitumen Road:** The process of road laying using waste plastics is designed and the technique is being implemented successfully for the construction of flexible roads at various places in India.

### Co-processing of Plastic waste in Cement Kiln:

Plastic waste generated from different cities and towns is a part of municipal solid waste (MSW). It is a matter of concern that disposal of plastic waste is causing many problems such as leaching impact on land and ground water, choking of drains, making land infertile, indiscriminate burning causing environmental hazards etc. Plastic waste, being non-biodegradable, is littered in most of the cities/towns and their-by giving an ugly appearance. It is estimated that approximately 15,342 tonnes/day (TPD) of plastic waste (on per capita basis) is generated in the country. To get rid of plastic waste disposal problems, Central Pollution Control Board (CPCB) in association with M. P. Pollution Control Board has taken initiative to use the plastic waste in cement plant at ACC Kymore (Katni, M. P.). The stack monitoring results, revealed that emission values are found below the standard set for Common Hazardous Waste Incinerators. After getting encouraging results, CPCB has granted permission to many cement plants to co-process the hazardous and non-hazardous (including plastic) waste in their kilns after trial burns.

Co-processing of plastic waste as an Alternative Fuel and Raw Material (AFR):Co-processing refers to the utilization of waste materials in industry process such as cement, production of lime or steel and power stations or any other large combustion plants. Co-processing shows replacement of primary fuel and raw material by waste recovering industry and material from waste. Waste materials, for instance, plastic waste used for co-processing are referred to as alternative fuels and raw material (AFR). Co-processing of plastic waste suggests advantages for cement industry as well as for the Municipal Authorities responsible for waste management. In other hand, cement producers can save fossil fuel and raw material consumption, contributing the more eco-efficient production. In addition, one of the advantages of recovery method used in existing facility would be, eradicating the need to invest on other plastic waste practices and to secure land filling.

Co-processing of Plastic waste in Cement Kiln: One of the most effective methods of recycling of plastics waste for recovery of energy is its use as an alternative fuel in cement kilns. Apart from recycling of plastic for making new products and saving energy, there are also projects which aim to turn plastic into new energy sources. Plastic is prepared from crude oil, which is the same raw material from which fuel is made. Thus, some scientists have made it their goal to turn waste plastic back to crude oil so that it can be reused for powering engines. With the help of this method, waste plastic is not only put to actual use, but it also helps to save the scarce crude oil resources left on earth. The high temperature used in the cement kilns gives a scope for use of even some type of plastic waste contaminated with toxic chemicals like pesticides and some other hazardous materials without creating any increased emissions in the air or water. No segregation or cleaning is required for such type of disposal. Low-end plastic waste, which creates a waste management problem, may provide the vital energy to the cement industry. At 10% replacement rate, 170 Cement Kilns in India could dispose of the entire plastic waste generated in the country today with additional benefit of reduction in the use of fossil fuel- coal.

Plasma Pyrolysis Technology (PPT): Plasma Pyrolysis is a technology, which put together the thermo-chemical properties of plasma with the pyrolysis process. The extreme and versatile heat generation ability of plasma pyrolysis technology enables it to dispose of all types of plastic waste.

Process Technology: In Plasma Pyrolysis, initially the plastic waste is fed into the primary chamber at 850 0 C through a feeder. The waste material dissociates into carbon monoxide, hydrogen, methane, higher hydrocarbons etc. Induced draft fan drains the pyrolysis gases and plastic waste into the secondary chamber. In this chamber, the pyrolysis gases are combusted in the presence of excess air. The inflammable gases catch fire because of high voltage spark. The temperature in the secondary chamber is maintained at 10500C. The hydrocarbon, hydrogen and CO are combusted into water and safe carbon dioxide. Conditions are maintained such that it eradicates the possibility of formation of toxic gases. The conversion of organic waste into non toxic gases (CO<sub>2</sub>, H<sub>2</sub>O) is more than 99%. The excessive conditions of plasma kill stable bacteria such as bacillus stereothermophilus and bacillus subtilis right away. Segregation of the waste is not necessary, since very high temperatures make sure the treatment of all types of waste without discrimination.

Conversion of Plastics Waste into Liquid Fuel: This technology is not very complicated. As feedstock, it can accept a broad range of plastics, including those that are unwashed, unsorted, or which are hard to recycle. Once the material is obtained, it can be cut up into small pieces prior to its utilization, but current advancements have led to the capability of putting larger pieces of plastic directly into the system. To start the process, waste is laden into a hopper with a forklift. The materials which can be loaded include plastic car bumpers, fuel tanks, product packaging, component holders, agricultural film, and pharmaceutical packaging. Natural gas is burnt to generate heat and get the process started once the hopper is in the reactor. At this point a catalyst helps in breaking the plastic hydrocarbons into shorter chain of molecules. The off-gases that are not going to be collected as fuel are used to produce heat and keep the process going. The fuel oil and diesel are condensed from a gaseous state into a liquid state, which are collected as the process continues. They are placed into temporary fuel tanks. The process is controlled by an automated system.

## **DATA COLLECTION**

Secondary Data:- the data collected for the present study is from different journals, magazine, news papers, etc.

## **CONCLUSION**

Plastic Waste Management has assumed great significance in present day context. Various schemes are being implemented to mitigate the impacts of plastic waste in India. Recycling is one such scheme for waste management of plastic products. It makes rising sense environmentally as well as economically and current trends demonstrate a considerable increase in the rate of recovery and recycling of plastic wastes. These trends are expected to continue, but some significant challenges still exist from both technological factors and from economic or social behaviour issues relating to the collection of recyclable wastes, and substitution for virgin material. Joined with efforts to increase the specification and use of recycled grades as replacement of virgin plastic, recycling of waste plastics is an efficient way to improve the environmental performance of the polymer industry

## **RECOMMENDATIONS**

When designing a recycling program, the city should identify markets for recycled materials. The characteristics of the market determine how recyclables should be collected, processed, and eventually sold [32]. To extend our model to the national level, we took U.S. Census data from 2000 which recorded the population density. We then tested each county. On the national level, the EPA should strongly encourage recycling programs for almost every county or region, particularly in denser, less rural regions. Team #1356, Page 18 of 20 In general, across the U.S., very small cities such as Price, Utah will incur losses from a recycling program. A drop-off program cannot be used to full advantage because much of the potential coverage area of one drop-off center lies beyond the city limits. In relatively large, densely populated cities such as Wichita, Kansas, dual-stream curbside collection is generally recommended to bring the highest profits. This is due to low participation in drop-off recycling; on average, only 15.5% of potentially covered households participate. The revenue benefits of a pay-as-you-throw initiative must be balanced against the cost of its unpopularity among citizens. A pay-as-you-throw initiative is generally recommended for small cities such as Price, Utah that seek to adopt a recycling program but incur losses no matter what the program. In these cases, a pay-as-you-throw initiative is recommended to offset losses to the city.

## **BIBLIOGRAPHY**

- Oehlmann J. et al., A critical analysis of the biological impacts of plasticizers on wildlife, *Phil. Trans. R. Soc. B* 364, 2047–2062. (doi:10.1098/rstb.2008.0242) (2009)
- DEFRA 2007 Waste strategy factsheets. See <http://www.defra.gov.uk/environment/waste/strategy/factsheets/land-filltax.htm> (26 November 2008) (2008)
- Gilpin R., Wagel D. and Solch J., Production, distribution, and fate of polychlorinated dibenzo-p-dioxins, dibenzofurans, and related organohalogenes in the environment. In *Dioxins and health* (eds A. Schecter & T. Gasiewicz), 2nd edn. Hoboken, NJ: John Wiley & Sons Inc. (2003)
- Amjad Khan, Gangadhar, Murali Mohan and Vinay Raykar, *Effective Utilisation of Waste Plastics in Asphaltting of Roads*, Project Report prepared under the guidance of R. Suresh and H. Kumar, Dept. of Chemical Engg., R.V. College of Engineering, Bangalore (1999)
- Siddiqui Javeriya, *A Case Study on Solid Waste Management in Mysore City*, M. Tech. (Environmental Engineering) Dissertation, Department of Civil Engineering, Madan Mohan Malaviya Engineering College, Gorakhpur (U. P.). (2013)